

## RIDEMAX IT 696 - Tekniska specifikationer



### Description

RIDEMAX IT 696 har en unik mönsterdesign och ett brett avtryck som ger utmärkt grepp vid körning på väg, även i vinterväglag. Däcket lämpar sig bäst för transporter och kommun/underhåll, tack vare egenskaper för höga hastigheter och det starka däckhöljet. Mönsterdesignen har tagits fram speciellt för tung tjänst och säkerställer ett lågt rullningsmotstånd som ger bättre bränsleekonomi och fantastisk stabilitet.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Traktor

Version	STANDARD
Type	TL
Tyre Size	300/80 R 24 IND (11.2 R 24)
LI/SS	133 A8/128 D

## Dimensions International Standard

Section Width (mm)	295
Overall Diameter (mm)	1090
Static Loaded Radius (mm)	501
Rolling Circumference (mm)	3296
SRI (mm)	525
Rim Rec	DW 10
ECE	E4-106R-002292

## Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	845	1045	1225	1420	1600	1800
50	910	1125	1320	1535	1725	1940
40	970	1195	1400	1625	1835	2060
30	1010	1245	1460	1700	1915	2150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 3/19/2025 11:47 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..