

## RIDEMAX IT 696 - Tekniska specifikationer



### Description

RIDEMAX IT 696 har en unik mönsterdesign och ett brett avtryck som ger utmärkt grepp vid körning på väg, även i vinterväglag. Däcket lämpar sig bäst för transporter och kommun/underhåll, tack vare egenskaper för höga hastigheter och det starka däckhöljet. Mönsterdesignen har tagits fram speciellt för tung tjänst och säkerställer ett lågt rullningsmotstånd som ger bättre bränsleekonomi och fantastisk stabilitet.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Traktor

Version	STANDARD
Type	TL
Tyre Size	300/80 R 24 IND (11.2 R 24)
LI/SS	133 A8/128 D

## Dimensions US Standard

Usa code	94033881
Section Width (inch)	11.6
Overall Diameter (inch)	42.9
Static Loaded Radius (inch)	19.7
Rolling Circumference (inch)	129.8
Rim Rec	DW 10
ECE	E4-106R-002292

## Load capacity (lbs)

mph / psi	17	23	29	35	41	46
40	1860	2300	2700	3130	3530	3970
30	2010	2480	2910	3380	3800	4280
25	2140	2630	3090	3580	4050	4540
20	2230	2740	3220	3750	4220	4740

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 3/19/2025 10:21 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..