

RIDEMAX IT 696 - Tekniska specifikationer



Description

RIDEMAX IT 696 har en unik mönsterdesign och ett brett avtryck som ger utmärkt grepp vid körning på väg, även i vinterväglag. Däcket lämpar sig bäst för transporter och kommun/underhåll, tack vare egenskaper för höga hastigheter och det starka däckhöljet. Mönsterdesignen har tagits fram speciellt för tung tjänst och säkerställer ett lågt rullningsmotstånd som ger bättre bränsleekonomi och fantastisk stabilitet.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Traktor

Version	STANDARD
Type	TL
Tyre Size	340/80 R 24 IND (12.4 R 24)
LI/SS	140 A8/135 D

Dimensions US Standard

Usa code	94033843
Section Width (inch)	13.5
Overall Diameter (inch)	45.4
Static Loaded Radius (inch)	20.5
Rolling Circumference (inch)	135.6
Rim Rec	DW 11
Rim Alt	W 10 ; W 12 ; DW 10
ECE	E4-106R-002293

Load capacity (lbs)

mph / psi	17	23	29	35	41	46
40	2260	2790	3260	3790	4280	4810
30	2440	3010	3530	4090	4610	5180
25	2590	3200	3750	4350	4910	5510
20	2690	3330	3900	4530	5100	5730

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 3/19/2025 11:19 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..