

## RIDEMAX IT 696 - Tekniska specifikationer



### Description

RIDEMAX IT 696 har en unik mönsterdesign och ett brett avtryck som ger utmärkt grepp vid körning på väg, även i vinterväglag. Däcket lämpar sig bäst för transporter och kommun/underhåll, tack vare egenskaper för höga hastigheter och det starka däckhöljet. Mönsterdesignen har tagits fram speciellt för tung tjänst och säkerställer ett lågt rullningsmotstånd som ger bättre bränsleekonomi och fantastisk stabilitet.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Traktor

Version	STANDARD
Type	TL
Tyre Size	420/65 R 24 IND
LI/SS	146 D/151 A8

## Dimensions US Standard

Usa code	94058464
TMPH	1
Section Width (inch)	16.5
Overall Diameter (inch)	45.6
Static Loaded Radius (inch)	20.9
Rolling Circumference (inch)	137.1
Rim Rec	DW 13 L; W13
Rim Alt	DW 15 L ; DW 14 L
ECE	E11-106R-005952

## Load capacity (lbs)

mph / psi	17	23	29	35	41	46	52	58
40	2650	3240	3640	4300	4890	5490	6020	6610
30	2850	3510	3920	4640	5290	5930	6500	7140
25	3040	3730	4190	4950	5630	6320	6920	7610
20	3170	3890	4360	5160	5870	6590	7220	7940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 3/19/2025 11:39 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..