

RIDEMAX IT 696 - Tekniska specifikationer



Description

RIDEMAX IT 696 har en unik mönsterdesign och ett brett avtryck som ger utmärkt grepp vid körning på väg, även i vinterväglag. Däcket lämpar sig bäst för transporter och kommun/underhåll, tack vare egenskaper för höga hastigheter och det starka däckhöljet. Mönsterdesignen har tagits fram speciellt för tung tjänst och säkerställer ett lågt rullningsmotstånd som ger bättre bränsleekonomi och fantastisk stabilitet.

UM

International Standard

Construction

RADIAL

Machinery

Lantbruk: Traktor

Version	STANDARD
Type	TL
Tyre Size	440/80 R 28 IND (16.9 R 28)
LI/SS	156 A8/151 D

Dimensions International Standard

Section Width (mm)	441
Overall Diameter (mm)	1415
Static Loaded Radius (mm)	634
Rolling Circumference (mm)	4288
SRI (mm)	675
Rim Rec	W 14 L
Rim Alt	W 15 L
ECE	E4-106R-002299

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	1620	2000	2345	2725	3070	3450
50	1765	2180	2555	2970	3345	3760
40	1880	2320	2720	3160	3560	4000
30	1955	2415	2830	3285	3700	4160

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..