

RIDEMAX IT 696 - Tekniska specifikationer



Description

RIDEMAX IT 696 har en unik mönsterdesign och ett brett avtryck som ger utmärkt grepp vid körning på väg, även i vinterväglag. Däcket lämpar sig bäst för transporter och kommun/underhåll, tack vare egenskaper för höga hastigheter och det starka däckhöljet. Mönsterdesignen har tagits fram speciellt för tung tjänst och säkerställer ett lågt rullningsmotstånd som ger bättre bränsleekonomi och fantastisk stabilitet.

UM

International Standard

Construction

RADIAL

Machinery

Lantbruk: Traktor

| | |
|-----------|--------------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 440/80 R 34 IND (16.9 R 34) |
| LI/SS | 159 A8/155 D |

Dimensions International Standard

| | |
|----------------------------|------------------|
| Section Width (mm) | 441 |
| Overall Diameter (mm) | 1567 |
| Static Loaded Radius (mm) | 704 |
| Rolling Circumference (mm) | 4775 |
| SRI (mm) | 750 |
| Rim Rec | DW 14 L |
| Rim Alt | DW 15 L; DW 16 L |
| ECE | E4-106R-002295 |

Load capacity (Kg)

| km/h / bar | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 |
|------------|------|------|------|------|------|------|
| 65 | 1820 | 2250 | 2635 | 3060 | 3450 | 3875 |
| 50 | 1935 | 2390 | 2800 | 3255 | 3665 | 4120 |
| 40 | 2055 | 2540 | 2975 | 3455 | 3895 | 4375 |
| 30 | 2145 | 2645 | 3100 | 3600 | 4060 | 4560 |

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..