

RIDEMAX IT 696 - Tekniska specifikationer



Description

RIDEMAX IT 696 har en unik mönsterdesign och ett brett avtryck som ger utmärkt grepp vid körning på väg, även i vinterväglag. Däcket lämpar sig bäst för transporter och kommun/underhåll, tack vare egenskaper för höga hastigheter och det starka däckhöljet. Mönsterdesignen har tagits fram speciellt för tung tjänst och säkerställer ett lågt rullningsmotstånd som ger bättre bränsleekonomi och fantastisk stabilitet.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Traktor

Version	STANDARD
Type	TL
Tyre Size	500/70 R 24 IND
LI/SS	157 A8/152 D

Dimensions US Standard

Usa code	94067862
Section Width (inch)	19.8
Overall Diameter (inch)	51.6
Static Loaded Radius (inch)	23.7
Rolling Circumference (inch)	155.7
Rim Rec	DW 16 L
Rim Alt	DW 15 L ; DW 18 L
ECE	E11-106R-007051

Load capacity (lbs)

mph / psi	17	23	29	35	41	46
40	3910	4780	5250	6180	6970	7830
30	4230	5160	5670	6680	7530	8450
25	4550	5560	6100	7190	8100	9090
20	4700	5730	6290	7430	8370	9390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 3/19/2025 10:57 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..