

## RM 500 - Tekniska specifikationer



### Description

RM 500 är ett radialdäck med stålbalte som lämpar sig för skördningsarbeten. Det har ett robust däckhölje och en speciell mönsterdesign som ger hög lastkapacitet och extra stor motståndskraft mot skärande underlag och punkteringar. Tack vare det stora avtrycket säkerställer RM 500 fantastisk tryckfördelning mot marken och utmärkt dragförmåga, samtidigt som jordpackningen minskar.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Lantbruk: Skördemaskin

Version	STEEL BELTED
Type	TL
Tyre Size	500/70 R 24
LI/SS	167 A8 / 155 A8
LI/SS DRIVE WHEEL	155 A8
LI/SS FREE ROLLING	167 A8

## Dimensions International Standard

Section Width (mm)	502
Overall Diameter (mm)	1310
Static Loaded Radius (mm)	572
Rolling Circumference (mm)	3907
SRI (mm)	625
Rim Rec	W 16 L
Rim Alt	W 15 L
ECE	E11-106R-005989

## Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8
40 Free Rolling	2290	2620	2945	3600	4145	4800	5450
40 Drive Wheel	1630	1860	2095	2560	3945	3410	3875

Printed on 4/26/2024 9:18 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..