

RM 500 - Tekniska specifikationer



Description

RM 500 är ett radialdäck med stålbalte som lämpar sig för skördningsarbeten. Det har ett robust däckhölje och en speciell mönsterdesign som ger hög lastkapacitet och extra stor motståndskraft mot skärande underlag och punkteringar. Tack vare det stora avtrycket säkerställer RM 500 fantastisk tryckfördelning mot marken och utmärkt dragförmåga, samtidigt som jordpackningen minskar.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Skördemaskin

| | |
|--------------------|-----------------|
| Version | STEEL BELTED |
| Type | TL |
| Tyre Size | 500/85 R 24 |
| LI/SS | 182 A8 / 170 A8 |
| LI/SS DRIVE WHEEL | 170 A8 |
| LI/SS FREE ROLLING | 182 A8 |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94061570 |
| Section Width (inch) | 20.5 |
| Overall Diameter (inch) | 57.5 |
| Static Loaded Radius (inch) | 24.5 |
| Rolling Circumference (inch) | 172.5 |
| Rim Rec | W 16 L |
| Rim Alt | W 15 L |
| ECE | E11-106R-005991 |

Load capacity (lbs)

| mph / psi | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 |
|-----------------|------|------|-------|-------|-------|-------|-------|-------|
| 25 Free Rolling | 7870 | 9560 | 11060 | 12740 | 14430 | 15550 | 17050 | 18740 |
| 25 Drive Wheel | 5560 | 6750 | 7800 | 8990 | 10180 | 10980 | 12040 | 13230 |

Printed on 4/26/2024 10:47 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..