

## ROCK GRIP E4 - Ladda ned faktablad



### Description

ROCK GRIP (E-4) är ett diagonaldäck avsett för truckar i gruvor och stenbrott. ROCK GRIP passar perfekt för de korta transporter där du behöver ett pålitligt däck som är både värmetåligt och tåligt mot skärskador.

### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: Stel dumper

| SIZE       | Version                | TRA Code | PR | RIM REC   | RIM ALT   | OW  | OD   | SLR  | RC   | Type |
|------------|------------------------|----------|----|-----------|-----------|-----|------|------|------|------|
| 14.00 - 25 | STANDARD               | E4       | 32 | 10.00/2.0 |           | 375 | 1410 | 649  | 4173 | TL   |
| 14.00 - 25 | STANDARD               | E4       | 24 | 10.00/2.0 |           | 375 | 1410 | 649  | 4173 | TL   |
| 14.00 - 25 | STANDARD               | E4       | 28 | 10.00/1.5 |           | 375 | 1410 | 649  | 4173 | TL   |
| 14.00 - 25 | STANDARD               | E4       | 28 | 10.00/1.5 |           | 375 | 1410 | 649  | 4173 | TT   |
| 14.00 - 25 | STANDARD               | E4       | 28 | 10.00/2.0 |           | 375 | 1410 | 649  | 4173 | TL   |
| 14.00 - 25 | STANDARD               | E4       | 28 | 10.00/2.0 |           | 375 | 1410 | 649  | 4173 | TT   |
| 14.00 - 25 | STANDARD               | E4       | 32 | 10.00/1.5 |           | 375 | 1410 | 649  | 4173 | TL   |
| 14.00 - 25 | STANDARD               | E4       | 24 | 10.00/1.5 |           | 375 | 1410 | 649  | 4173 | TL   |
| 14.00 - 25 | STANDARD               | E4       | 24 | 10.00/2.0 |           | 375 | 1410 | 649  | 4173 | TT   |
| 14.00 - 25 | STANDARD               | E4       | 24 | 10.00/1.5 |           | 375 | 1410 | 649  | 4173 | TT   |
| 16.00 - 25 | STANDARD               | E4       | 28 | 11.25/2.0 | 13.00/2.0 | 470 | 1525 | 699  | 4514 | TL   |
| 16.00 - 25 | STANDARD               | E4       | 32 | 11.25/2.0 | 13.00/2.0 | 470 | 1525 | 699  | 4514 | TL   |
| 18.00 - 25 | STANDARD               | E4       | 40 | 13.00/2.5 | 15.00/2.5 | 510 | 1650 | 753  | 4885 | TL   |
| 18.00 - 25 | STANDARD               | E4       | 32 | 13.00/2.5 | 15.00/2.5 | 510 | 1650 | 753  | 4885 | TL   |
| 18.00 - 25 | STANDARD               | E4       | 36 | 13.00/2.5 | 15.00/2.5 | 510 | 1650 | 753  | 4885 | TL   |
| 18.00 - 25 | STANDARD               | E4       | 40 | 13.00/2.5 | 15.00/2.5 | 510 | 1650 | 753  | 4885 | TT   |
| 18.00 - 25 | STANDARD               | E4       | 24 | 13.00/2.5 | 15.00/2.5 | 510 | 1650 | 753  | 4885 | TT   |
| 18.00 - 25 | STANDARD               | E4       | 32 | 13.00/2.5 | 15.00/2.5 | 510 | 1650 | 753  | 4885 | TT   |
| 18.00 - 33 | CUT RESISTANT COMPOUND | E4       | 40 | 13.00/2.5 |           | 510 | 1887 | 869  | 5586 | TL   |
| 18.00 - 33 | CUT RESISTANT COMPOUND | E4       | 36 | 13.00/2.5 |           | 510 | 1887 | 869  | 5586 | TL   |
| 18.00 - 33 | STANDARD               | E4       | 36 | 13.00/2.5 |           | 510 | 1887 | 869  | 5586 | TT   |
| 18.00 - 33 | STANDARD               | E4       | 36 | 13.00/2.5 |           | 510 | 1887 | 869  | 5586 | TL   |
| 18.00 - 33 | STANDARD               | E4       | 40 | 13.00/2.5 |           | 510 | 1887 | 869  | 5586 | TT   |
| 18.00 - 33 | STANDARD               | E4       | 40 | 13.00/2.5 |           | 510 | 1887 | 869  | 5586 | TL   |
| 18.00 - 33 | STANDARD               | E4       | 44 | 13.00/2.5 |           | 510 | 1887 | 869  | 5586 | TL   |
| 21.00 - 35 | CUT RESISTANT COMPOUND | E4       | 40 | 15.00/3.0 |           | 580 | 2040 | 943  | 6068 | TL   |
| 21.00 - 35 | CUT RESISTANT COMPOUND | E4       | 36 | 15.00/3.0 |           | 580 | 2040 | 943  | 6068 | TL   |
| 21.00 - 35 | STANDARD               | E4       | 36 | 15.00/3.0 |           | 580 | 2040 | 943  | 6068 | TL   |
| 21.00 - 35 | STANDARD               | E4       | 40 | 15.00/3.0 |           | 580 | 2040 | 943  | 6068 | TL   |
| 24.00 - 35 | CUT RESISTANT COMPOUND | E4       | 48 | 17.00/3.5 |           | 655 | 2190 | 1003 | 6482 | TL   |
| 24.00 - 35 | STANDARD               | E4       | 48 | 17.00/3.5 |           | 655 | 2190 | 1003 | 6482 | TL   |
| 24.00 - 49 | CUT RESISTANT COMPOUND | E4       | 48 | 17.00/3.5 |           | 655 | 2531 | 1184 | 7498 | TL   |
| 24.00 - 49 | STANDARD               | E4       | 42 | 17.00/3.5 |           | 655 | 2531 | 1184 | 7498 | TL   |
| 24.00 - 49 | STANDARD               | E4       | 48 | 17.00/3.5 |           | 655 | 2531 | 1184 | 7498 | TL   |
| 27.00 - 49 | CUT RESISTANT COMPOUND | E4       | 48 | 19.50/4.0 |           | 740 | 2695 | 1253 | 7985 | TL   |
| 27.00 - 49 | CUT RESISTANT COMPOUND | E4       | 54 | 19.50/4.0 |           | 740 | 2695 | 1253 | 7985 | TL   |
| 27.00 - 49 | STANDARD               | E4       | 54 | 19.50/4.0 |           | 740 | 2695 | 1253 | 7985 | TL   |
| 27.00 - 49 | STANDARD               | E4       | 48 | 19.50/4.0 |           | 740 | 2695 | 1253 | 7985 | TL   |
| 30.00 - 51 | CUT RESISTANT COMPOUND | E4       | 52 | 22.00/4.5 |           | 830 | 2910 | 1350 | 8615 | TL   |
| 30.00 - 51 | STANDARD               | E4       | 46 | 22.00/4.5 |           | 830 | 2910 | 1350 | 8615 | TL   |
| 30.00 - 51 | STANDARD               | E4       | 52 | 22.00/4.5 |           | 830 | 2910 | 1350 | 8615 | TL   |

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..