

## ROCK GRIP IND4 (ECH) - Tekniska specifikationer



### Description

ROCK GRIP PORT INDUSTRIAL IND-4 (ECH) är ett däck med vinkelskikt konstruerat för tomcontainerhanterare inom olika användningsområden, exempelvis industri och stålverk. ROCK GRIP-specialblandningen ger extra hög värmetålighet samt enastående stabilitet och hållbarhet.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industri: Tomcontainerhanterare

Version	PORT INDUSTRIAL
Type	TL
Tyre Size	14.00 - 24

## Dimensions International Standard

Ply Rating	28
Overall Width (mm)	375
Overall Diameter (mm)	1410
Static Loaded Radius (mm)	647
Rolling Circumference (mm)	4173
Rim Rec	10.00 W
TRA Code	IND4

## Load capacity (Kg)

km/h / bar	10.00
10	13500

Printed on 4/27/2024 5:05 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..