

ROCK GRIP L4 - Tekniska specifikationer



Description

ROCK GRIP (L-4) är ett diagonaldäck för hjullastare som används i tunga lastningsmiljöer och på tuffa underlag. Den specialdesignade skär- och rivtåliga gummiblandningen i slitbanan minimerar antalet punkteringar och efterföljande stilleståndstid. Det djupa mönstret (L-4) ger däckets längre livslängd.

UM

US Standard

Construction

 BIAS

Machinery

Industri: Bulldozer • Hjullastare

Version	STANDARD
Type	TL
Tyre Size	14.00 - 25

Dimensions US Standard

Usa code	94031160
Ply Rating	32
Overall Width (inch)	14.8
Overall Diameter (inch)	55.5
Static Loaded Radius (inch)	25.6
Rolling Circumference (inch)	164.3
Rim Rec	10.00/1.5
TRA Code	L4

Load capacity (lbs)

mph / psi	145
5	23100

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 4:12 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..