

ROCK GRIP (T) - Tekniska specifikationer



Description

ROCK GRIP (E-4) passar bäst för lastväxlare som används för korta transporter av tunga laster i stenbrott och gruvor. Den speciella gummiblandningen i slitbanan minimerar antalet skärskador och punkteringar vid körning på mycket tuffa underlag. ROCK GRIP (E-4) har exceptionell dragkraft och extra lång livslängd.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Väg- och terränggående lastbil • Stel dumper

Version	STANDARD
Type	TT
Tyre Size	10.00 - 20

Dimensions International Standard

Ply Rating	18
Overall Width (mm)	280
Overall Diameter (mm)	1090
Rim Rec	7.5
Rim Alt	7.0

Load capacity (Kg)

km/h / bar	7.60
90 LS/LD	2800

Printed on 4/26/2024 8:14 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..