

ROCK GRIP (T) - Tekniska specifikationer



Description

ROCK GRIP (E-4) passar bäst för lastväxlare som används för korta transporter av tunga laster i stenbrott och gruvor. Den speciella gummiblandningen i slitbanan minimerar antalet skärskador och punkteringar vid körning på mycket tuffa underlag. ROCK GRIP (E-4) har exceptionell dragkraft och extra lång livslängd.

UM

US Standard

Construction

❖ BIAS

Machinery

OTR: Väg- och terränggående lastbil • Stel dumper

| | |
|-----------|------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 11.00 - 20 |

Dimensions US Standard

| | |
|-------------------------|----------|
| Usa code | 94062416 |
| Ply Rating | 18 |
| Overall Width (inch) | 11.8 |
| Overall Diameter (inch) | 44.7 |
| Rim Rec | 8.0 |
| Rim Alt | 7.5 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 110 |
| 55 LS/LD | 6610 |

Printed on 4/26/2024 6:21 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..