

## ROCK STAR IND4 - Tekniska specifikationer



### Description

ROCK START PORT IND-4 har utformats särskilt för tomma containerhanterare och gaffeltruckar. Förutom utmärkt dragkraft ger den unika slitbanan överlägset motstånd mot skär- och skrapskador. ROCK START PORT IND-4 säkerställer enastående lastkapacitet och överlägsen hållbarhet.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industri: Tomcontainerhanterare • Gaffeltruck

Version	PORT INDUSTRIAL
Type	TL
Tyre Size	14.00 - 24

## Dimensions US Standard

Usa code	94058204
Ply Rating	32
Overall Width (inch)	15.4
Overall Diameter (inch)	56.1
Static Loaded Radius (inch)	25
Rolling Circumference (inch)	171.3
Rim Rec	10.00 WA
Rim Alt	10.00 VA
TRA Code	IND4

## Load capacity (lbs)

mph / psi	145
5	31250

Printed on 4/27/2024 11:57 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..