

# RT 747 AGRO INDUSTRIAL - Tekniska specifikationer



## Description

RT 747 AGRO INDUSTRIAL är ett industriradialdäck för lantbruket som lämpar sig för kompakthjullastare och teleskoplastare. De extra breda däckklackarna ger utmärkt dragförmåga och imponerande stabilitet under lyftarbeten. Däcket har designats med en speciell gummblandning med motståndskraft mot skärande underlag och punkteringar och möjliggör tunga laster. RT 747 AGRO INDUSTRIAL är det rätta svaret på alla utmaningar inom allmän lantbruksverksamhet som kräver enastående mångsidighet.

## UM

International Standard

## Construction

 RADIAL

## Machinery

Lantbruk: Kompakthjullastare • Teleskoplastare  
Industri: Kompakthjullastare • Teleskoplastare

Version	STANDARD
Type	TL
Tyre Size	11L R 16
LI/SS	122 A8/B

## Dimensions International Standard

Section Width (mm)	290
Overall Diameter (mm)	850
Rim Rec	W 8
Rim Alt	W 10 L
ECE	E11-106R-005769

## Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.2	2.4	2.6
10	1265	1530	1790	1920	2055	2200
30	940	1165	1385	1500	1610	---
40	880	1085	1295	1395	1500	---

Printed on 4/25/2024 4:05 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..