

RT 747 AGRO INDUSTRIAL - Tekniska specifikationer



Description

RT 747 AGRO INDUSTRIAL är ett industriradialdäck för lantbruket som lämpar sig för kompakthjullastare och teleskoplastare. De extra breda däckklackarna ger utmärkt dragförmåga och imponerande stabilitet under lyftarbeten. Däcket har designats med en speciell gummblandning med motståndskraft mot skärande underlag och punkteringar och möjliggör tunga laster. RT 747 AGRO INDUSTRIAL är det rätta svaret på alla utmaningar inom allmän lantbruksverksamhet som kräver enastående mångsidighet.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Kompakthjullastare • Teleskoplastare
Industri: Kompakthjullastare • Teleskoplastare

Version	STANDARD
Type	TL
Tyre Size	11L R 16
LI/SS	122 A8/B

Dimensions US Standard

Usa code	94062737
Section Width (inch)	11.4
Overall Diameter (inch)	33.5
Rim Rec	W 8
Rim Alt	W 10 L
ECE	E11-106R-005769

Load capacity (lbs)

mph / psi	17	23	29	32	35	38
5	2790	3370	3950	4230	4530	4850
15	2070	2570	3050	3310	3550	---
25	1940	2390	2850	3080	3310	---

Printed on 4/25/2024 6:00 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..