



RT 851 - Ladda ned faktablad



Description

RT 851 är ett R-1-däck som är specialkonstruerat för traktorer och tillämpningar inom gräsmark. Den speciella, rundade däckklacksdesignen har tagits fram för att minska förekomsten av skador på gräsmark och spirande grödor samt jordpackningen. Det robusta däckhöljet i nylon med slitstarka polyesterbälten ger extraordinär dragförmåga samt ökad lastkapacitet.

UM

International Standard

Construction

RADIAL

Machinery

Lantbruk: Traktor

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
14.9L R 20 (375/75 R 20)	STANDARD	R1	119 A8/B	W 13	W 11; W 12; W 14	378	1100	498	3286	525	TL	E11-106R-002989

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/13/2025 2:29 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..