

RT 857 - Tekniska specifikationer



Description

RT 857 är ett däck designat för jordbearbetning. Det robusta däcksölet ger utmärkt hållbarhet och dragförmåga. Gummiblandningen har hög motståndskraft mot stubb, skärande underlag och punkteringar.

UM

International Standard

Construction

 RADIAL

Machinery

Lantbruk: Traktor

Version	STANDARD
Type	TL
Tyre Size	320/85 R 28 (12.4 R 28)
LI/SS	124 A8/B

Dimensions International Standard

Section Width (mm)	329
Overall Diameter (mm)	1255
Static Loaded Radius (mm)	577
Rolling Circumference (mm)	3779
SRI (mm)	600
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E4-106R-000757
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	880	1025	1170	1315	1460	1600
40	880	1025	1170	1315	1460	1600
30	945	1100	1255	1410	1565	1715
10 LT	1180	1375	1570	1760	1955	2145
10 HT	945	1100	1255	1410	1565	1715

Printed on 2/2/2023 10:47 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..