

SAND KING - Tekniska specifikationer



Description

SAND KING är ett blockmönsterdäck för släpvagnar som används för transportändamål. Det ger utmärkt dragkraft på sandiga underlag och bästa möjliga markkontakt.

UM

International Standard

Construction

 BIAS

Machinery

Industri: Släpvagn

Version	STANDARD
Type	TT
Tyre Size	7.50 - 16

Dimensions International Standard

Ply Rating	10
Section Width (mm)	215
Overall Diameter (mm)	820
Static Loaded Radius (mm)	378
Rolling Circumference (mm)	2471
Rim Rec	5.50 F SDC
Rim Alt	6.00 G
ECE	E11-106R-005309

Load capacity (Kg)

km/h / bar	5.20
65 LS	1215

Printed on 4/27/2024 4:29 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..