



SIERRA MAX PRO - Tekniska specifikationer



Description

SIERRA MAX PRO är det perfekta däcket från BKT för alla terrängfordon, såväl ATV- som SSV-fordon. Radialkonstruktionen och det speciella, breddade avtrycket ger mjukare körning och optimerad dragförmåga både i sidled och framåt. De robusta, specialdesignade däckklackarna har tagits fram specifikt för att ge utmärkt dragförmåga och bra grepp i terrängen. Funktionerna är en garanti för extremt bekväm körning tillsammans med säkerhet och körkontroll. SIERRA MAX PRO erbjuder utmärkt prestanda i all slags terräng, från hårdpackad mark till lös jord.

UM

US Standard

Construction



Machinery

Lantbruk: Fyrhjuling

Version	STANDARD
Type	
Tyre Size	AT 27 X 11 R 14
LI/SS	56 N

Dimensions US Standard

Usa code	94066155
Section Width (inch)	11.2
Overall Diameter (inch)	27.9
Static Loaded Radius (inch)	13.2
Rolling Circumference (inch)	84.4
Rim Rec	9.00
Star Rating	***
ECE	E11-75R-005098

Load capacity (lbs)

mph / psi	18
87	495

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 4:49 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..