

SIERRA MAX - Tekniska specifikationer



Description

SIERRA MAX är BKT:s däck som passar till både terrängkörning och gräsmatte- och trädgårdsarbeten. Radialkonstruktionen ger betydligt jämnare och bekvämare körning i extrem terräng som öken, eller på leriga och steniga underlag. Det specialdesignade och bredare mönstret ger enastående dragförmåga framåt och i sidled.

UM

International Standard

Construction

 RADIAL

Machinery

Lantbruk: Fyrhjuling

Version	STANDARD
Type	TL
Tyre Size	AT 27 X 9 R 14
LI/SS	50 N

Dimensions International Standard

Section Width (mm)	230
Overall Diameter (mm)	700
Static Loaded Radius (mm)	316
Rolling Circumference (mm)	2070
Rim Rec	7.00
Star Rating	***
ECE	E11-75R-005099

Load capacity (Kg)

km/h / bar	0.50
140	190

Printed on 4/26/2024 5:01 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..