

## SKID POWER HD (A) - Tekniska specifikationer

### Description

SKID POWER HD (A) är avsett för användning på kompaktlastare i bygg- och anläggningsbranschen. Det extra djupa mönstret och skyddet för sidoväggen ger det här däck ett utomordentligt skydd mot skär- och skrapskador samt enastående pålitlighet. SKID POWER HD (A) är idealiskt att använda på lösa underlag och vid tunga arbeten.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industri: Kompaktlastare



Version	IMPLEMENT
Type	TL
Tyre Size	15 - 19.5
LI/SS	146 A8

## Dimensions International Standard

Ply Rating	14
Section Width (mm)	400
Overall Diameter (mm)	1019
Static Loaded Radius (mm)	463
Rolling Circumference (mm)	3075
Rim Rec	11.75
Rim Alt	12.25
ECE	E11-106R-003656

## Load capacity (Kg)

km/h / bar	4.85
40	3000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/13/2024 7:50 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..