

SKID POWER HD (A) - Tekniska specifikationer

Description

SKID POWER HD (A) är avsett för användning på kompaktlastare i bygg- och anläggningsbranschen. Det extra djupa mönstret och skyddet för sidoväggen ger det här däck ett utomordentligt skydd mot skär- och skrapskador samt enastående pålitlighet. SKID POWER HD (A) är idealiskt att använda på lösa underlag och vid tunga arbeten.



UM

US Standard

Construction

 BIAS

Machinery

Industri: Kompaktlastare

Version	STANDARD
Type	TL
Tyre Size	18 X 8.5 - 8
LI/SS	97 A2

Dimensions US Standard

Usa code	94030422
Ply Rating	8
Section Width (inch)	8.3
Overall Diameter (inch)	18.1
Static Loaded Radius (inch)	8.1
Rolling Circumference (inch)	53.4
Rim Rec	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-005559

Load capacity (lbs)

mph / psi	44
5	1630
10	1290
15	1190

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/13/2024 6:19 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..