

## SKID POWER HD (A) - Tekniska specifikationer

### Description

SKID POWER HD (A) är avsett för användning på kompaktlastare i bygg- och anläggningsbranschen. Det extra djupa mönstret och skyddet för sidoväggen ger det här däck ett utomordentligt skydd mot skär- och skrapskador samt enastående pålitlighet. SKID POWER HD (A) är idealiskt att använda på lösa underlag och vid tunga arbeten.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industri: Kompaktlastare



Version	IMPLEMENT
Type	TL
Tyre Size	27 X 8.5 - 15
LI/SS	102 A8

## Dimensions US Standard

Usa code	94056033
Ply Rating	8
Section Width (inch)	8.6
Overall Diameter (inch)	26.6
Static Loaded Radius (inch)	12.8
Rolling Circumference (inch)	78.9
Rim Rec	7 JA
ECE	E11-106R-003540

## Load capacity (lbs)

mph / psi	61
25	1875

Printed on 4/26/2024 4:41 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..