

## SKID POWER PLUS - Tekniska specifikationer



### Description

SKID POWER PLUS är avsett för användning på kompaktlastare i bygg- och anläggningsbranschen. De bredare blocken ger utmärkt dragkraft och bättre självrensande egenskaper. Det extra djupa mönstret och det förbättrade skyddet för sidoväggen ger det här däck ett utomordentligt skydd mot skär- och skrapskador samt enastående pålitlighet. SKID POWER PLUS är idealiskt att använda på lösa underlag. Den breda kontaktytan ger däck ett utmärkt stabilitet.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Industri: Kompaktlastare

Version	SPECIAL
Type	TL
Tyre Size	10 - 16.5

## Dimensions US Standard

Usa code	94057412
Ply Rating	10
Section Width (inch)	9.9
Overall Diameter (inch)	30.5
Rim Rec	8.25

## Load capacity (lbs)

mph / psi	75
5	4710
10	3710
15	3440

Printed on 4/23/2024 3:52 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..