

## SKID POWER SK - Tekniska specifikationer



### Description

SKID POWER SK är avsett för användning på kompaktlastare i bygg- och anläggningsbranschen. Sidoväggs- och fälgskydden samt det djupa mönstret ger däckets en längre livscykel.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industri: Kompaktlastare

Version	IMPLEMENT
Type	TL
Tyre Size	10 - 16.5
LI/SS	116 A8

## Dimensions International Standard

Ply Rating	8
Section Width (mm)	270
Overall Diameter (mm)	775
Static Loaded Radius (mm)	355
Rolling Circumference (mm)	2286
Rim Rec	8.25
ECE	E11-106R-003543

## Load capacity (Kg)

km/h / bar	4.10
40	1250

Printed on 4/26/2024 9:43 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..