

SKID POWER - Tekniska specifikationer



Description

SKID POWER är avsett för användning på kompaktlastare i bygg- och anläggningsbranschen. Det har utmärkt dragkraft och förbättrade självrensande egenskaper. Det extra djupa mönstret och det extra skyddet för sidoväggen ger det här däckets ett utomordentligt skydd mot skär- och skrapskador samt enastående pålitlighet. SKID POWER är idealiskt att använda på lösa underlag.

UM

US Standard

Construction

 BIAS

Machinery

Industri: Kompaktlastare

Version	IMPLEMENT
Type	TL
Tyre Size	10 - 16.5
LI/SS	116 A8

Dimensions US Standard

Usa code	94055661
Ply Rating	8
Section Width (inch)	10
Overall Diameter (inch)	30.5
Static Loaded Radius (inch)	14
Rolling Circumference (inch)	90
Rim Rec	8.25
ECE	E11-106R-003534

Load capacity (lbs)

mph / psi	60
25	2755

Printed on 4/24/2024 5:33 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..