SKID POWER - Tekniska specifikationer

Description

SKID POWER är avsett för användning på kompaktlastare i bygg- och anläggningsbranschen. Det har utmärkt dragkraft och förbättrade självrensande egenskaper. Det extra djupa mönstret och det extra skyddet för sidoväggen ger det här däcket ett utomordentligt skydd mot skär- och skrapskador samt enastående pålitlighet. SKID POWER är idealiskt att använda på lösa underlag.

UM

US Standard

Construction

BIAS

Machinery

Industri: Kompaktlastare

Version	IMPLEMENT
Type	TL
Tyre Size	14 - 17.5
LI/SS	141 A8

Dimensions US Standard

Usa code	94056125
Ply Rating	14
Section Width (inch)	14
Overall Diameter (inch)	37
Static Loaded Radius (inch)	16.7
Rolling Circumference (inch)	109.2
Rim Rec	10.5
ECE	E11-106R-003609

Load capacity (lbs)

mph / psi	80
25	5675

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 10/12/2024 10:08 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..