

SKID MAX SR-SKIDDER - Tekniska specifikationer



Description

SKID MAX SR-SKIDDER är BKT:s nya radialdäck helt i stål, specialkonstruerat för användning i krävande arbetsmiljöer på hårda, förstärkta underlag – exempelvis vägunderhåll och avfallshantering med kompaktlastare, grävlastare och teleskoplastare. Tack vare den robusta konstruktionen med däckhöljet i stål och stålbalten erbjuder däckets överlägsna hållbarhet och hög lastkapacitet.

Det breda och robusta däckmönstret är utformat med ett kontinuerligt ribbat mittparti som, i kombination med materialblandningen som är antistatisk och har extremt hög motståndskraft mot nötning och slitning, garanterar utmärkt dragförmåga och lång livslängd för produkten. Den extra tjocka sidoväggen och det hårda höljet ger också imponerande hållbarhet och minimerar risken för punkteringar och skador, vilket minskar maskinens stilleståndstid.

Det specialdesignade fälgskyddet säkerställer skydd mot punkteringar och skador på hjulet i fälg- och flänsområdet. Och sist men inte minst ger SKID MAX SR-SKIDDER även utmärkt komfort och stabilitet i det dagliga arbetet.

UM

International Standard

Construction

 RADIAL

Machinery

Industri: Hjullastare • Kompaktlastare • Teleskoplastare

Version	INDUSTRIAL
Type	TL
Tyre Size	260/70 R 16.5 (10 R 16.5)
LI/SS	129 A8/B

Dimensions International Standard

Overall Width (mm)	263
Overall Diameter (mm)	776
Static Loaded Radius (mm)	352
Rolling Circumference (mm)	2367
Rim Rec	8.25
Rim Alt	7.50 ; 9.00
ECE	E11-106R-006809

Load capacity (Kg)

km/h / bar	5.00
40	1850
50	1850

Printed on 4/27/2024 10:19 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..