

SM 48 (GK) - Tekniska specifikationer



Description

SM 48 (GK) är ett gokartdäck. Den släta slitbanan ger utmärkt prestanda vid sportig körning. Shore A hårdhet 48.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Gokart

Version	STANDARD
Type	TL
Tyre Size	10 X 4.5 - 5

Dimensions International Standard

Section Width (mm)	130
Overall Diameter (mm)	260
Rim Rec	4.5

Load capacity (Kg)

km/h / bar	4.00
-	130

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/8/2024 5:09 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..