

## SM 53 - Ladda ned faktablad



### Description

SM 53 är avsett för hjullastare som används i gruvdrift och för lastning under jord. Det har hög stabilitet och det släta slitbanemönstret ger ett utmärkt skydd mot skärskador.

### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: Underjordiskt gruvfordon

| SIZE      | Version  | TRA Code | PR | RIM REC | RIM ALT | OW  | OD   | SLR | RC   | Type |
|-----------|----------|----------|----|---------|---------|-----|------|-----|------|------|
| 9.00 - 20 | STANDARD | L3S      | 16 | 7.0     |         | 266 | 1040 | 472 | 3080 | TT   |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 9/20/2024 1:28 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..