

SM 53 - Ladda ned faktablad



Description

SM 53 är avsett för hjullastare som används i gruvdrift och för lastning under jord. Det har hög stabilitet och det släta slitbanemönstret ger ett utmärkt skydd mot skärskador.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Underjordiskt gruvfordon

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
9.00 - 20	STANDARD	94041510	L3S	16	7.0		10.5	40.9	18.6	121.3	TT

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 9/20/2024 2:25 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..