

SM 54 IND-4S - Tekniska specifikationer

Description

SM 54 IND-4S har utvecklats speciellt för tomma containerhanterare och sträckstaplare i intermodala/logistiska applikationer. De har hög stabilitet i lyftläge såväl som en djup och smidig slitbanekonstruktion, vilket ger utmärkt skärmotstånd för att säkerställa en förlängd däcklivscykel.



UM

US Standard

Construction

 BIAS

Machinery

Industri: Reachstacker

Version	INDUSTRIAL
Type	TL
Tyre Size	16.00 - 25

Dimensions US Standard

Usa code	94015610
Ply Rating	28
Overall Width (inch)	16.9
Overall Diameter (inch)	57.9
Static Loaded Radius (inch)	26.6
Rolling Circumference (inch)	171.4
Rim Rec	11.25/2.0
Rim Alt	13.00/2.0
TRA Code	L4S

Load capacity (lbs)

mph / psi	131
5	34200

Printed on 4/20/2024 5:16 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..