

## SM 54 M IND-4S - Tekniska specifikationer



### Description

SM 54 M IND-4S är en modifierad version av SM 54-mönstret. Den låga mönsterprofilen resulterar i en stor kontaktyta och därmed längre livslängd för däck. Däcket är specialkonstruerat för tomcontainerhanterare och reachstackers inom intermodala transporter/logistiktillämpningar. SM 54 M har hög stabilitet i lyftläge och en djup och slät mönsterdesign som gör det utomordentligt skär- och punkteringsbeständigt.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industri: Reachstacker

Version	PORT INDUSTRIAL
Type	TL
Tyre Size	18.00 - 33

## Dimensions International Standard

<b>Ply Rating</b>	40
<b>Overall Width (mm)</b>	535
<b>Overall Diameter (mm)</b>	1895
<b>Static Loaded Radius (mm)</b>	840
<b>Rolling Circumference (mm)</b>	5609
<b>Rim Rec</b>	13.00/2.5
<b>TRA Code</b>	IND-4S

## Load capacity (Kg)

km/h / bar	10.00
10	27000

Printed on 4/26/2024 6:37 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..