

SM 54 M IND-4S - Ladda ned faktablad



Description

SM 54 M IND-4S är en modifierad version av SM 54-mönstret. Den låga mönsterprofilen resulterar i en stor kontaktyta och därmed längre livslängd för däck. Däcket är specialkonstruerat för tomcontainerhanterare och reachstackers inom intermodala transporter/logistiktillämpningar. SM 54 M har hög stabilitet i lyftläge och en djup och slät mönsterdesign som gör det utomordentligt skär- och punkteringsbeständigt.

UM

International Standard

Construction

 BIAS

Machinery

Industri: Reachstacker

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
18.00 - 25	PORT INDUSTRIAL	IND-4S	40	13.00/2.5	15.00/2.5	528	1650	750	4880	TL
18.00 - 33	PORT INDUSTRIAL	IND-4S	40	13.00/2.5		535	1895	840	5609	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/13/2025 2:56 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..