

## SM 55 IND-5S - Tekniska specifikationer



### Description

SM 55 IND-5S är särskilt avsett för reach stacker-truckar och containertruckar. Den speciella gummiblandningen är motståndskraftig mot avskavningar, ger en utökad livslängd på asfalt och betongytor och en utmärkt stabilitet för fordon i lyftläge.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industri: Containerhanterare

Version	PORT SPECIAL
Type	TL
Tyre Size	18.00 - 25

## Dimensions US Standard

Usa code	94039609
Ply Rating	40
Overall Width (inch)	20.4
Overall Diameter (inch)	65.6
Static Loaded Radius (inch)	30.1
Rolling Circumference (inch)	201.5
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	IND5

## Load capacity (lbs)

mph / psi	145
5	50625

Printed on 4/26/2024 8:23 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..