

SM 55 IND-5S - Ladda ned faktablad



Description

SM 55 IND-5S är särskilt avsett för reach stacker-truckar och containertruckar. Den speciella gummiblandningen är motståndskraftig mot avskavningar, ger en utökad livslängd på asfalt och betongytor och en utmärkt stabilitet för fordon i lyftläge.

UM

International Standard

Construction

 BIAS

Machinery

Industri: Containerhanterare

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
12.00 - 24	PORT INDUSTRIAL	IND5	20	8.5	7.33 V ; 8 ; 8.00 V ; 8.50 V	310	1275	594	3777	TT
18.00 - 25	PORT SPECIAL	IND5	40	13.00/2.5	15.00/2.5	517	1665	765	5118	TL

Printed on 4/26/2024 4:33 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..