SM 55 L5S - Tekniska specifikationer

Description

SM 55 (L-5S) är ett diagonaldäck för användning i gruvdrift under jord. Den specialdesignade skär- och rivtåliga gummiblandningen i slitbanan minimerar antalet punkteringar och efterföljande stilleståndstid. Det extra djupa L-5S-mönstret garanterar en längre livscykel. Däcket finns även tillgängligt i en version med stålbälten.

UM

International Standard

Construction

BIAS

Machinery

OTR: Dumper med lågprofil • Underjordiskt gruvfordon

Version	STANDARD
Type	TT
Tyre Size	12.00 - 24

Dimensions International Standard

Ply Rating	20
Overall Width (mm)	310
Overall Diameter (mm)	1275
Static Loaded Radius (mm)	594
Rolling Circumference (mm)	3777
Rim Rec	8.5
Rim Alt	7.33 V ; 8 ; 8.00 V ; 8.50 V
TRA Code	L5S

Load capacity (Kg)

km/h / bar	8.25
10	6900
15	6005
25	5520

Printed on 4/28/2024 2:00 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..