

## SNOW - RIDE (A) - Tekniska specifikationer



### Description

SNOW RIDE lämpar sig särskilt för kommun- och underhållsarbeten i vinterförhållanden med kompakthjullastare och glidstyrda kompaktlastare. Däcket har utmärkt dragförmåga och är idealiskt för användning på is och snö. Det specialdesignade mönstret eliminerar halkrisken och säkerställer en längre livslängd för däcket.

### UM

International Standard

### Construction

 BIAS

### Machinery

Lantbruk: Kompakthjullastare  
Industri: Kompaktlastare

Version	STANDARD
Type	TL
Tyre Size	17.5/65 - 20

## Dimensions International Standard

Ply Rating	10
Section Width (mm)	445
Overall Diameter (mm)	1095
Static Loaded Radius (mm)	493
Rolling Circumference (mm)	3285
Rim Rec	W 14 L

## Load capacity (Kg)

km/h / bar	2.40
10	3195

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 12/9/2024 8:16 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..