

SNOW - RIDE (A) - Tekniska specifikationer



Description

SNOW RIDE lämpar sig särskilt för kommun- och underhållsarbeten i vinterförhållanden med kompakthjullastare och glidstyrda kompaktlastare. Däcket har utmärkt dragförmåga och är idealiskt för användning på is och snö. Det specialdesignade mönstret eliminerar halkrisken och säkerställer en längre livslängd för däcket.

UM

US Standard

Construction

 BIAS

Machinery

Lantbruk: Kompakthjullastare
Industri: Kompaktlastare

Version	STANDARD
Type	TL
Tyre Size	17.5/65 - 20

Dimensions US Standard

Usa code	94041381
Ply Rating	10
Section Width (inch)	17.5
Overall Diameter (inch)	43.1
Static Loaded Radius (inch)	19.4
Rolling Circumference (inch)	129.3
Rim Rec	W 14 L

Load capacity (lbs)

mph / psi	35
5	7040

Printed on 4/23/2024 4:44 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..