

SNOW - RIDE (B) - Tekniska specifikationer

Description

SNOW-RIDE är särskilt lämpat för körning av kompaktlastare i vinterväglag. Däcket har utmärkt dragförmåga och är idealiskt för användning på is och snö. Det specialdesignade mönstret eliminerar halkrisken.

UM

International Standard

Construction

 BIAS

Machinery

Industri: Bulldozer • Hjullastare



Version	STANDARD
Type	TL
Tyre Size	23.5 - 25

Dimensions International Standard

Ply Rating	16
Section Width (mm)	612
Overall Diameter (mm)	1630
Static Loaded Radius (mm)	693
Rolling Circumference (mm)	4800
Rim Rec	19.50/2.5
TRA Code	L2

Load capacity (Kg)

km/h / bar	3.00
10	9500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 3/22/2025 2:11 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..