

SR 713 - Tekniska specifikationer



Description

SR 713 är ett radialdäck helt i stål med VF-teknologi för jordbrukstillämpningar. Däcket har ett flerskiktigt stålbälteshölje och flera mönsterribbor som säkerställer lågt rullmotstånd och jämnt mönsterslitage. Tack vare sitt stora avtryck ger det här VF-däcket minskad jordpackning. SR 713 är överlägset i både prestanda och pålitlighet samt erbjuder enastående hastigheter på vägen.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Arbetsfordon

Version	STANDARD
Type	TL
Tyre Size	VF 265/70 R 19.5
LI/SS	146 D

Dimensions US Standard

Usa code	94070305
Overall Width (inch)	10
Overall Diameter (inch)	34.4
Static Loaded Radius (inch)	15.4
Rolling Circumference (inch)	102.8
Rim Rec	7.50
Rim Alt	8.25
ECE	E11-106R-007581
TRA Code	I1

Load capacity (lbs)

mph / psi	75
40	6600

Printed on 12/5/2023 2:16 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..