

ST 180 - Tekniska specifikationer



Description

ST 180 är ett däck som har utvecklats för transportverksamhet med släpvagnar och arbetsfordon. Det specialdesignade mönstret säkerställer en längre livslängd för däcket tack vare minskat slitage. ST 180 finns i flera versioner: en version med "stålförstärkt bälte" som säkerställer ökad motståndskraft mot punkteringar, medan specialversionen ger hög motståndskraft mot skärande underlag och punkteringar.

UM

International Standard

Construction

 BIAS

Machinery

Lantbruk: Arbetsfordon • Släpvagn

Version	STANDARD
Type	TL
Tyre Size	ST 205/75 D 15 (F 78 - 15)

Dimensions International Standard

Ply Rating	6
Section Width (mm)	195
Overall Diameter (mm)	702
Static Loaded Radius (mm)	327
Rolling Circumference (mm)	2103
Rim Rec	5½ J
Rim Alt	5 J ; 6 J ; 7 J

Load capacity (Kg)

km/h / bar	3.50
40	825

Printed on 12/9/2023 3:16 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..