



STEER GRIP - Tekniska specifikationer



Description

STEER GRIP är det perfekta däcket för styrande axlar på lastväxlare. Den breda mittribban med raka block gör att det här däcket passar på frirullande hjul och det förbättrade greppet ger utmärkt prestanda på både blöta och torra vägar. Den speciella gummiblandningen i slitbanan kombinerar bästa möjliga slitstyrka med skydd mot skär- och skrapskador och det kraftiga höljet ger däcket en längre livscykel.

UM

US Standard

Construction

❖ BIAS

Machinery

OTR: Väg- och terränggående lastbil

Version	STANDARD
Type	TT
Tyre Size	11.00 - 20

Dimensions US Standard

Usa code	94052103
Ply Rating	18
Overall Width (inch)	11.8
Overall Diameter (inch)	44.1
Static Loaded Radius (inch)	20.7
Rolling Circumference (inch)	133.7
Rim Rec	8.0
Rim Alt	7.5
Tread Depth	29

Load capacity (lbs)

mph / psi	110
55 LS/LD	6610

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/22/2025 3:22 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..