

STEER GRIP - Tekniska specifikationer



Description

STEER GRIP är det perfekta däck för styrande axlar på lastväxlare. Den breda mittribban med raka block gör att det här däck passar på frirullande hjul och det förbättrade greppet ger utmärkt prestanda på både blöta och torra vägar. Den speciella gummiblandningen i slitbanan kombinerar bästa möjliga slitstyrka med skydd mot skär- och skrapskador och det kraftiga höljet ger däck en längre livscykel.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Väg- och terränggående lastbil

Version	STANDARD
Type	TT
Tyre Size	12.00 - 24

Dimensions US Standard

Usa code	94049363
Ply Rating	20
Overall Width (inch)	12.2
Overall Diameter (inch)	49.1
Static Loaded Radius (inch)	23.1
Rolling Circumference (inch)	149
Rim Rec	8.5
Rim Alt	8.0

Load capacity (lbs)

mph / psi	115
50 LS/LD	8540

Printed on 4/25/2024 4:03 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..