

SUPER SAND - Ladda ned faktablad



Description

SUPER SAND passar utmärkt för släpvagnar som används på sandiga underlag vid höga temperaturer. Det har hög flytförmåga och är idealiskt för alla användningsområden som kräver hög manövrerbarhet.

UM

International Standard

Construction

 BIAS

Machinery

Industri: Släpvagn

| SIZE | Version | PR | RIM REC | RIM ALT | SW | OD | Type |
|------------|----------|----|---------|---------|-----|------|------|
| 9.00 - 15 | STANDARD | 6 | 7.00 | | 275 | 854 | TT |
| 9.00 - 16 | STANDARD | 8 | 6.50 H | 6.00 G | 255 | 885 | TT |
| 14.00 - 20 | STANDARD | 12 | 10.00 V | 10.00 W | 385 | 1225 | TT |
| 14.00 - 20 | STANDARD | 16 | 10.00 V | 10.00 W | 385 | 1225 | TT |
| 14.00 - 20 | STANDARD | 18 | 10.00 V | 10.00 W | 385 | 1225 | TT |
| 16.00 - 20 | STANDARD | 16 | 10.00 W | | 415 | 1305 | TT |

Printed on 4/26/2024 10:49 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..