

SUPER SAND - Ladda ned faktablad



Description

SUPER SAND passar utmärkt för släpvagnar som används på sandiga underlag vid höga temperaturer. Det har hög flytförmåga och är idealiskt för alla användningsområden som kräver hög manövrerbarhet.

UM

US Standard

Construction

 BIAS

Machinery

Industri: Släpvagn

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	Type
9.00 - 15	STANDARD	94014286	6	7.00		10.8	33.6	TT
9.00 - 16	STANDARD	94014279	8	6.50 H	6.00 G	10	34.8	TT
14.00 - 20	STANDARD	94025558	12	10.00 V	10.00 W	15.2	48.2	TT
14.00 - 20	STANDARD	94025763	16	10.00 V	10.00 W	15.2	48.2	TT
14.00 - 20	STANDARD	94028504	18	10.00 V	10.00 W	15.2	48.2	TT
16.00 - 20	STANDARD	94048359	16	10.00 W		16.3	51.4	TT

Printed on 4/26/2024 12:01 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..