

SUPER TRAX HD - Tekniska specifikationer



Description

SUPER TRAX HD har konstruerats speciellt för gaffeltruckar som används till tung materialhantering, exempelvis hamn- och gruvdrift. Det extra djupa mönstret är tillverkat av en unik, slitstark gummiblandning som ger längre livslängd. SUPER TRAX HD har ett starkt däckhölje och förstärkt sidovägg, vilket leder till utmärkt stabilitet och manövrering i lyftläge. Det specialdesignade fälgskyddet skyddar mot punkteringar och skador på hjulet i fälg- och flänsområdet.

UM

International Standard

Construction

 BIAS

Machinery

Industri: Gaffeltruck

Version	STANDARD
Type	TT
Tyre Size	6.50 - 10

Dimensions International Standard

Ply Rating	12
Section Width (mm)	195
Overall Diameter (mm)	600
Static Loaded Radius (mm)	282
Rolling Circumference (mm)	1838
Rim Rec	5.00 F
Rim Alt	5.50 F

Load capacity (Kg)

km/h / bar	9.00
25 LOAD WHEEL	2145
25 STEER WHEEL	1650
10 OTHER VEHICLES	2145
25 OTHER VEHICLES	1650
STATIC SIDE LOADER	2490

Printed on 4/20/2024 7:27 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..