

SUPER TRAX HD - Tekniska specifikationer



Description

SUPER TRAX HD har konstruerats speciellt för gaffeltruckar som används till tung materialhantering, exempelvis hamn- och gruvdrift. Det extra djupa mönstret är tillverkat av en unik, slitstark gummiblandning som ger längre livslängd. SUPER TRAX HD har ett starkt däckhölje och förstärkt sidovägg, vilket leder till utmärkt stabilitet och manövrering i lyftläge. Det specialdesignade fälgskyddet skyddar mot punkteringar och skador på hjulet i fälg- och flänsområdet.

UM

US Standard

Construction

 BIAS

Machinery

Industri: Gaffeltruck

Version	STANDARD
Type	TT
Tyre Size	6.50 - 10

Dimensions US Standard

Usa code	94052936
Ply Rating	12
Section Width (inch)	7.7
Overall Diameter (inch)	23.6
Static Loaded Radius (inch)	11.1
Rolling Circumference (inch)	72.4
Rim Rec	5.00 F
Rim Alt	5.50 F

Load capacity (lbs)

mph / psi	131
15 LOAD WHEEL	4730
15 STEER WHEEL	3635
5 OTHER VEHICLES	4730
15 OTHER VEHICLES	3635
STATIC SIDE LOADER	5490

Printed on 4/20/2024 6:06 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..